

AHM-PIPE

Submarine Cable Protection System

AHM-Pipe

Assembly Instruction

The AHM-Pipe Cable Protection System is easy to fit - whether simultaneously during the installation onboard a vessel/barge or during a post-lay activity subsea/onshore. The identical, self-locking half-shells are assembled into a flexible, abrasion and impact protective pipe cover to the required length, whereby each pipe segment is simply secured to the next.

Step 1:

Place the first half-shell under the product.



Step 2:

Place the second half-shell directly over the bottom half-shell, then lower and engage to the bottom half-shell.



Step 3:

Lift up the center assembly and position the next bottom half-shell ensuring that the stub-end (male) is securely located in the clamp ball-end (female).



Step 4:

Repeat steps two and three until the required length of articulated pipe has been reached.



Note:

Even though the assembled pipe cover is self-locking, we recommend that the free-supplied nuts and bolts are applied to secure both the first and the last pipe segments as well as in 10m intervals along the length of the pipe cover.

AHMTEC GmbH
Hafenstrasse 6c
D-26789 Leer/Germany
Tel.: +49 (0)491 20980 500
Fax: +49 (0)491 20980 509
Email: info@ahmtec.de
Web: www.ahmtec.de

AHMTEC
cable protection systems